



Pace Analytical Services, Inc.
723 Kasota Ave. SE
Minneapolis, MN 55414

Phone: 612.656.1100
Fax: 612.656.1181

www.pacelabs.com

LABORATORY ANALYSIS REPORT

DATE: 2010/06/03
CLIENT: Pionetics Corporation
151H Old County Road
San Carlos, CA 94070

PAGE: 1 of 7
PROJECT: 619
COLLECTED BY: AB
PROJECT REC'D: 2010-03-04
PROJECT DESC: Linx 140-120V

CONTACT: Eric Nyberg

Pace Analyticals Product Testing Division received 2 Linx 140-120V (s) for the analysis presented in the following report.

All data reported is associated with quality control that met method, EPA, NSF/ANSI or internal laboratory specification. Any exceptions are noted in a footnote or narrative format.

Pace Analytical Services, Inc. appreciates the opportunity to provide you with this product testing service. We value your feedback, would you please take a few minutes to access our customer satisfaction survey at: <http://www.pacelabs.com/my-account/customer-survey.html> . If you have any questions or comments regarding this report, please feel free to contact us.

Sincerely,

Enclosure



Pace Analytical Services, Inc.
723 Kasota Ave. SE
Minneapolis, MN 55414

Phone: 612.656.1100
Fax: 612.656.1181

www.pacelabs.com

LABORATORY ANALYSIS REPORT

PROJECT: 619

PAGE: 2 of 7

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 006997	Description: Influent	Volume: 10 Unit Volume
-----------------------	------------------------------	-------------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Alkalinity (wc)	14	mg/L	1.0	EPA 310.1	2010-05-17	2010-05-20
Conductivity	93	uS/cm	1	EPA 120.1	2010-05-17	2010-05-17
Hardness (wc)	20.0	mg/L	1.0	EPA 130.2	2010-05-17	2010-05-19
Low pH Selenium	121.00	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
pH (wc)	6.54	(None)	NA	EPA 150.1	2010-05-17	2010-05-17
Phosphorus (wc)	<0.05	mg/L	0.05	SM 4500-P	2010-05-17	2010-05-19
Pressure (psi)	60	psi	NA	(None)	2010-05-17	2010-05-17
Temperature (wc)	22.5	°C	NA	EPA 150.1	2010-05-17	2010-05-17
Total Dissolved Solids (wc)	33 ¹⁶	mg/L	10	EPA 160.1	2010-05-17	2010-05-28
Turbidity (wc)	<1.0	NTU	1.0	EPA 180.1	2010-05-17	2010-05-17

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007003	Description: Linx140-120V #3	Volume: 10 Unit Volume
-----------------------	-------------------------------------	-------------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	4	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	96	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.401	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	0.74	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	>99	%	NA	EPA 200.8	2010-05-17	2010-05-21

As a mutual protection to clients, the public, and ourselves, all documentation prepared by Pace Analytical Services, Inc., including proposals and reports, are submitted in confidence and may not be published in whole or in part, without written consent. In addition, the name of Pace Analytical Services, Inc. may not be used in any advertisement or other publication without written approval.

LABORATORY ANALYSIS REPORT

PROJECT: 619

PAGE: 4 of 7

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007007	Description: Linx140-120V #3	Volume: 5.7 Liters
-----------------------	-------------------------------------	---------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	3	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	97	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.401	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	1.50	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	98.8	%	NA	EPA 200.8	2010-05-17	2010-05-21

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007008	Description: Linx140-120V #4	Volume: 5.7 Liters
-----------------------	-------------------------------------	---------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	2	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	98	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.361	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	1.10	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	>99	%	NA	EPA 200.8	2010-05-17	2010-05-21

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007009	Description: Linx140-120V #3	Volume: 8.5 Liters
-----------------------	-------------------------------------	---------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	3	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	97	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.401	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	1.60	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	98.7	%	NA	EPA 200.8	2010-05-17	2010-05-21



NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007010	Description: Linx140-120V #4	Volume: 8.5 Liters
-----------------------	-------------------------------------	---------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	2	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	98	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.361	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	1.20	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	99.0	%	NA	EPA 200.8	2010-05-17	2010-05-21

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007011	Description: Linx140-120V #3	Volume: 11.4 Liters
-----------------------	-------------------------------------	----------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	2	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	98	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.401	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	1.70	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	98.6	%	NA	EPA 200.8	2010-05-17	2010-05-21

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007012	Description: Linx140-120V #4	Volume: 11.4 Liters
-----------------------	-------------------------------------	----------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	2	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	98	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.361	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	1.50	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	98.8	%	NA	EPA 200.8	2010-05-17	2010-05-21



Pace Analytical Services, Inc.
723 Kasota Ave. SE
Minneapolis, MN 55414

Phone: 612.656.1100
Fax: 612.656.1181

www.pacelabs.com

LABORATORY ANALYSIS REPORT

PROJECT: 619

PAGE: 6 of 7

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007013	Description: Linx140-120V #3	Volume: 13.6 Liters
-----------------------	-------------------------------------	----------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	2	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	98	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.401	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	1.70	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	98.6	%	NA	EPA 200.8	2010-05-17	2010-05-21

NSF/ANSI Standard 53 - 2009 Low pH Selenium Reduction

Sample: 007014	Description: Linx140-120V #4	Volume: 13.6 Liters
-----------------------	-------------------------------------	----------------------------

<u>Compound</u>	<u>Results</u>	<u>Units</u>	<u>Reporting Limit</u>	<u>Method</u>	<u>Date Collected</u>	<u>Date Analyzed</u>
Conductivity	2	uS/cm	1	EPA 120.1	2010-05-17	2010-05-18
Conductivity % Red	98	%	NA	EPA 120.1	2010-05-17	2010-05-18
Flow Rate	0.361	GPM	NA	(None)	2010-05-17	2010-05-17
Low pH Selenium	1.30	ug/L	0.50	EPA 200.8	2010-05-17	2010-05-21
Low pH Selenium % Red	98.9	%	NA	EPA 200.8	2010-05-17	2010-05-21



PERFORMANCE SUMMARY

Contaminant	Low pH Selenium	
Number of Systems Tested	2	
Rated Claim	11.40	Liters
Performance Indicating Device (PID)	Yes	
Total Test Volume	14	Liters
Percentage of Rated Claim	123	PERCENT
Manufacturers Rated Flow Rate	0.50	GPM
Average Flow Rate (all devices)	0.381	GPM
Average Test Influent	121	ug/L
Average Effluent (all devices)	1.31	ug/L
Maximum Allowable Effluent Level	50	ug/L
Failure Point - Linx140-120V #3	Didn't Fail	Liters
Failure Point - Linx140-120V #4	Didn't Fail	Liters

This report has been reviewed for technical accuracy and completeness. The analyses were performed using EPA or other approved methodologies and the results were reported on an "as received" basis unless otherwise noted. These results relate only to the items tested.

NA = Not Applicable

su - Standard Units

UV - Unit Volume

mg/L = milligrams per Liter

ug/L = micrograms per Liter

GPM = Gallons Per Minute

NTU = Nephelometric Turbidity Unit

(wc) = Water Characteristics are for monitoring purposes only, quality control samples may or may not have been performed.

16 - Analysis conducted outside the recognized method holding time.

END OF DOCUMENT